

Maine State Library

Digital Maine

Transportation Documents

Transportation

12-31-2003


Application for Driveway/Entrance Permit : Bangor, Appendix G, Part 3, 2003

Maine Department of Transportation

Follow this and additional works at: https://digitalmaine.com/mdot_docs

This image shows a full page of blank graph paper. The grid consists of small, uniform squares formed by thin, light gray lines. There are no margins, text, or other markings on the page.

- 1) Provide, erect and maintain all necessary barricades, lights, warning signs and other devices to safeguard traffic properly while the work is in progress.
- 2) At no time cause the highway to be closed to traffic.
- 3) Where the drive/entrance is located within a curb, curb and gutter, and/or sidewalk section, completely remove the existing curb, curb and gutter, and/or sidewalk as may be required to create the drive/entrance and restore drainage. All driveways/entrances abutting sidewalk sections shall meet the requirements set forth in the Americans with Disabilities Act of 1990, 42 U.S.C. §§ 12132 et seq.
- 4) Obtain, deliver to side and install any culverts and/or drainage structures necessary for drainage; the size, type and length of such culverts or structures shall be as specified in the permit pursuant to 23 M.R.S.A. § 705. **All culverts and/or drainage structures shall be new.**
- 5) Complete construction of proposed driveway/entrance within twelve months of commencement of construction.
- 6) Comply with all applicable federal, state, and municipal regulations and ordinances.
- 7) Not alter, without the express written consent of the MDOT, any culverts or drainage swales within MDOT right-of-way.
- 8) File a copy of the approved driveway/entrance permit with the affected municipality or LURC, as appropriate, within 5 business days of receiving the MDOT approval; and mail a copy of the approved driveway/entrance permit to the immediate abutters within 5 business days of receiving the MDOT approval.
- 9) Shall construct and maintain the entrance side slopes to be no steeper than the adjacent roadway side slopes, but in no case to be steeper than 3 horizontal to 1 vertical, unless the side slope is behind existing roadway guardrail, in which case it shall be no steeper than 2 horizontal to 1 vertical.
- 10) Notify the MDOT of a proposed change to use served by driveway/entrance when increase in traffic flow is expected to occur.



The owner shall assume the defense of, and pay all damages, fines, and penalties for which he/she shall become liable, and shall indemnify and safe harmless said Department, its representatives, agents and employees from liability, actions against all suite, claims, damages for wrongful death, personal injuries or property damage suffered by any person or association which results from the willful or negligent action or inaction of the owner/applicant/agent and in proceedings of every kind arising out of the construction and maintenance of said entrance(s), including snow removal. Nothing herein shall, nor is intended to, waive and defense, immunity or limitation of liability which may be available to the MDOT, their officers, agents or employees under the Maine Tort Claims Act or any other privileges and/or immunities provided by law.

Date Filed:

Signature of Owner/Applicant/Agent